


企业标准

SPECIFICATION FOR SCREEN CLOTH



筛网制造标准：
MANUFACTURED FOLLOWING THESE REGULATIONS:
ISO-14315:1997
ISO-4783/3:1981
ISO-2194:1991

重型筛网具有高耐磨性，可用在筛分岩石、碎石、石灰石等行业。

- ▶ 高碳钢材质——耐磨性好
- ▶ 不锈钢材质——耐腐蚀性好
- ▶ 其他材质——一般行业应用

High tensile screen cloth is commonly used in heavy duty applications for scalping and sizing of rocks, aggregates, limestone, etc.

They are woven in sizes to suite most vibrating screens and are available in:

High Tensile Steel-Abrasion resistance

Stainless Steel-Corrosion re

Monel.Brass,etc. -General applications

Stainless parameters 不锈钢参数

序号No	牌号 Grade	化学成分 % Chemical Composition			
		C	Ni	Mn	Cr
1	304	≤0.08	8.0-11.0	≤2.0	18.0-20.0
2	321	≤0.08	9.0-12.0	≤2.0	17.0-19.0
3	316	≤0.08	10.0-14.0	≤2.0	16.0-18.5
4	2205	≤0.03	4.5-6.5	2.5-3.5	21.0-24.0
5	2507	≤0.03	6-8	≤1.2	24-26

筛网规格

SPECIFICATION FOR SCREEN CLOTH

Aperture Square Weave	Light duty Wire Dia kg/m ² OA%			Medium Wire Dia kg/m ² OA%			Heavy Duty Wire Dia kg/m ² OA%		
2.00							1.37	7.1	35
3.15				2.00	9.9	37	2.50	14.1	31
4.0	2.00	8.50	44	2.50	12.2	38	3.05	16.8	32
5.0	2.00	7.80	51	2.50	16.6	44	3.05	14.7	38
5.6	2.50	9.80	48	3.05	13.7	41	4.00	21.2	34
6.35	2.50	8.89	51	3.05	12.6	46	4.00	19.6	38
6.8	2.50	9.00	51	3.05	10.0	44	4.00	19.7	37
7.1	2.50	8.80	55	3.05	11.9	48	4.00	18.3	41
8	2.50	10.80	54	4.00	16.9	44	5.00	24.4	38
9	3.05	9.80	55	4.00	15.6	48	5.00	22.7	44
10	3.05	9.10	58	4.00	14.5	51	5.00	21.2	44
11.2	3.05	10.40	54	5.00	19.6	48	5.60	28.6	44
12.5	4.00	12.30	57	5.00	18.1	51	5.60	20.0	47
14	4.00	16.70	54	5.00	20.0	51	6.80	24.6	48
16	5.00	15.10	58	5.60	19.5	56	6.80	22.6	51
18	5.00	14.50	58	6.80	20.7	55	7.10	25.0	51
20	5.60	14.00	61	6.80	19.2	58	7.10	24.0	54
22	5.60	17.60	61	7.10	21.5	57	8.00	26.7	54
25	6.80	16.10	64	7.10	20.1	60	8.00	24.6	57
28	7.00	14.70	63	8.00	19.0	61	9.00	27.8	57
32	8.00	20.60	64	9.00	26.0	60	10.00	30.4	58
38	8.00	18.70	67	9.00	28.1	64	10.00	27.9	61
40	9.00	21.00	67	10.00	25.4	64	11.20	31.1	61
45	9.00	19.50	69	10.00	23.4	67	11.20	28.4	64
50	10.00	23.20	69	11.20	26.0	67	12.50	31.8	64
56	10.00	19.20	72	11.20	28.7	69	12.50	29.0	67
63	10.00	17.40	75	11.20	24.5	72	12.50	25.1	70
76.2	10.00	14.80	78	11.20	16.0	75	12.50	20.0	73
80	10.00	16.00	79	11.20	17.5	72	12.50	21.5	75
90	10.00	14.00	81	11.20	15.7	79	12.70	19.4	77
100	10.00	10.00	82	11.20	14.3	81	12.70	17.6	79

Other Specifications are also available please check with our sales team

其他的规格也可以定制，请与我们的销售团队联系。

